



Telecel[®] BSE24-8G40

High-density, environmentally-hardened, long-life battery for back-up and renewable energy

Overview

Telecel[®] utilizes lithium ferrous phosphate (LiFePO₄) battery technology and represents a leap forward in price, safety and reliability. Compared to lead-acid batteries, the cost of Telecel batteries is at least 20% lower over the first five years of life and offers even greater savings over the total projected life of the battery of 10 to 12 years*. In addition, the initial cost is at least 20% less than competing lithium batteries.

Applications

Ideal for battery backup, renewable energy and generator cut-over, both on-grid and off-grid, Telecel provides safe, compact high-density energy storage for wireless sites, WiFi, DAS, WiMAX, and other infrastructure.

Replace Lead-Acid Batteries

Replacing existing lead-acid batteries with Telecel is simple. The 24-volt units have a similar footprint to standard 12-volt lead-acid batteries, mount on existing battery trays and are fitted with Anderson PowerPole housings for quick, easy connections**.

Reduce Energy Costs

With its 3000+ cycles, Telecel can power a site during daily peak electric rates and recharge during off-peak, reducing the utility bill by up to 30%*. This cycling capability also supports future installation of renewable energy generation, reducing utility bills by an additional 25%*.

Wide Operating Temperatures

Providing full rated capacity over a wide temperature range and all the way up to maximum charge/discharge current, Telecel has up to 37% longer run-time than lead-acid, for the same rated capacity.

Features

- ❖ Series/parallel configurations for 24 and 48 V systems
- ❖ Safe, high-density energy storage and backup
- ❖ Lightweight at one-third the weight of lead-acid
- ❖ Compact at half the volume of lead-acid
- ❖ On-grid and off-grid applications
- ❖ Wide operating temperature range
- ❖ Long life - up to 10 times the life of lead-acid in unconditioned enclosures

*Based on typical network deployment. Actual cost benefit varies with application.

**Some applications may require the addition of a 1RU Battery Multiplexer™ unit.

Electrical Performance and Connections

Nominal Capacity		42 Ah (1142 Wh)
Internal Resistance		<1.0 milliohms
Power Connection		SBS75X Anderson PowerPole
Voltage	Charge	28.8
	Open Circuit	26.8
	95% Discharged	23.2
Charge	Maximum	1C (40 A)
	Self Discharge	<3 % per month
Discharge	Maximum	2C (80 A)

Temperature Derating

-20°C (-4°F)	21%
+55°C (+131°F)	1%

Temperature

Charge	0° to +55°C (32° to +131°F)
Discharge	-20° to +55°C (-4° to +131°F)
Maximum Recommended	+75°C (167°F)
Long-Term Shell Resistance	+130°C (266°F)
Transient Shell Resistance	+170°C (338°F)

Size and Weight

	Single Pack	(2) 48V String
Height [†]	227 mm (8.94 inches)	227 mm (8.94 inches)
Width	119 mm (4.68 inches)	238 mm (9.37 inches)
Depth (Length)	378 mm (14.89 inches)	378 mm (14.89 inches)
Weight (as shipped)	15 kg (33.1 lbs)	30 kg (66.1 lbs)

[†] Recommend additional 15 mm of height above unit for working clearance

Cycle and Standby Life

Depth of Discharge	Cycles	Estimated Years [‡]
80%	2000	5
70%	3000	8
25%	8000	20
Float/Standby	N/A	10 to 15

[‡] Based on one cycle per day.

Constant Power Output to 24 V (watts at 25°C) (Single Pack)

Hours of runtime:	1	1115
	4	256
	8	132
	10	114
	12	94
	24	47

Specifications are subject to change without notice



Battery Street Energy, Inc.
www.batterystreetenergy.com